SOLDER SUFFIX	CUSTOMER TERMINAL	RoHS	LEAD(Pb)–FREE
LF3	Sn100%	Yes	Yes

compliant RoHS WE–MIDCOM









ELECTRICAL SPECIFICATIONS @ 25°C unless otherwise noted:

INDUCTANCE:	350µH min., 100kHz, 100mV, 8mADC, J1–J2; J3–J6, Lp.
DIELECTRIC RATING:	1500Vrms for 1 minute between P1–J1(tie P1+P3).
TURNS RATIO/POLARITY:	(P1–P2):(J1–J2) = 1:1, ±2%. (P3–P6):(J3–J6) = 1:1, ±2%.
INSERTION LOSS:	–1.0dB typ., 1MHz – 65MHz.
RETURN LOSS:	–18dB typ., 1M – 30MHz. –16dB typ., 30M – 45MHz. –14dB typ., 45M – 60MHz. –12dB typ., 60M – 80MHz.
CROSSTALK:	–33dB typ., 1MHz – 100MHz.
COMMON MODE REJECTION:	–35dB typ., 1MHz – 100MHz.

OPERATING TEMPERATURE RANGE: 0°C to +70°C.

REV.	DATE
6A	4/07

AGENCY NUMBER	
UL60950–1	E205930

Packaging Specifications

Method: Tube
PKG–0524
www.midcom–inc.com

Unless otherwise specified:
Tolerances: Fractions: ±1/64
Angles: ±1° Decimals: ±.010[.25]

This drawing is dual dimensioned. Dimensions in brackets are in millimeters.

DRAWING TITLE
TRANSFORMER
10/100Mbs
eiSos p/n: 7499011216

Midcom www.midcom–inc.com

REVISIONS: SEE SHEET 1

DRAWING NO.
MIC24013–5204T–LF3

SCALE ---

SHEET 2 OF 6